



[More Info](#) | [Get Quote](#)

Rainlogger 5

Model 3002

The Rainlogger 5 is an inexpensive datalogger designed to record the tips of a standard tipping-bucket rain gauge. This compact and durable field unit offers long-term reliability and convenience with a battery that lasts up to 10 years, and ESD (electrostatic discharge) protection with an ABS housing.

The event time stamp and total rainfall per time period is logged in non-volatile memory, which holds up to 100,000 readings. Sampling is event based, as the Rainlogger 5 records and saves each tip of the tipping-bucket as it happens.

Detailed Data

Levellogger customers can add rainfall data to their water level monitoring networks using the intuitive Levellogger Software. The Rainlogger 5 provides easy incorporation of precipitation data into existing Levellogger data. Rainfall data can allow correlation between precipitation events and changes in groundwater or surface water levels.

The Rainlogger 5 is compatible with all Solinst Levellogger 5 communication and deployment accessories. Logged data can be downloaded direct to a PC, your smart device using the Solinst Levellogger App, or to a DataGrabber 5 data transfer device. This versatile logger has the ability to integrate into a Solinst Telemetry System and has the option to communicate using SDI-12 protocol.

Advantages

- Single-eye optical for fast, reliable communication
- ABS housing provides excellent ESD protection
- Memory for up to 100,000 time stamped readings
- Low maintenance with 10 year battery
- Designed to be used with most tipping-buckets
- Compatible with Solinst Telemetry Systems



[GET QUOTE >](#)



Operation

The Rainlogger 5 is simply programmed with the user-friendly Levellogger Software. A Field Reader 5 or Desktop Reader 5 connects the Rainlogger 5 to a laptop or desktop PC and the Levellogger Software automatically detects the attached Rainlogger.

The Rainlogger 5 is easily deployed in the field, using a 3-pin connector cable attached to the rain gauge.

Data downloading can be 'All Data', 'Append Data', or 'Data Dump' at any time. Data can be displayed in graph or table format and exported to other programs. The Rainlogger 5 has self-test capability, reliable memory and the ability to upgrade firmware.

Applications

- Measuring local precipitation
- Determining peak rainfall events
- Stormwater management
- Remote monitoring of watersheds
- Ideal for correlating precipitation events to:
 - Groundwater and surface water data
 - Watershed and drainage basin studies
 - Agricultural and forestry studies

Technical Specifications

Battery Life	10 years (logging 2 parameters/10 minutes)
Clock Accuracy (typical)	+/- 1 minute/year
Operating Temperature	-20°C to 80°C
Maximum # Readings	100,000 readings
Communication	Optical high-speed: 57,600 bps with USB
Sampling Mode	Event Based, Real Time View
Sampling Rate	Variable - records each tip
Size	22 mm x 160 mm (7/8"x 6.3")
Weight	44 grams (1.6 oz)
Wetted Materials	ABS, Delrin®, Viton®
Rain Gauge Requirement	Standard tipping-bucket with normally-open or closed style reed switch output



Levellogger 5 App Interface

A smart alternative for programming, data collection, viewing and sharing, is the Levellogger 5 App Interface that uses *Bluetooth*® wireless technology to connect all Solinst dataloggers to your smart device using the Solinst Levellogger App (see Model 3001 Solinst Levellogger 5 App Interface data sheets).



®The Apple logo is a trademark of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Google Play is a trademark of Google Inc.
The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Solinst Canada Ltd. is under license.

© Delrin and Viton are registered trademarks of DuPont Corp.